

InGaAs 2 – 3 mm Quadrant PIN Preamplifier Module



CMC Electronics' 264-339838 series is a combination of InGaAs quadrant PIN receivers with four (4) built-in trans-impedance amplifiers in a 1-inch 12-lead TO-can package.

Customizations to bandwidth, rise time and responsivity will be available upon request.

Features

- 2 – 3 mm diameter quadrant InGaAs PIN
- 40 MHz bandwidth
- Low noise Equivalent Power (NEP)
- Spectral Response: 1000 – 1600 nm
- Eye safe operating band
- Common Cathode configuration
- Hermetically Sealed 1-inch TO-can

Applications

- Free-Space Optical (FSO) Communication
- Precision Guided Munition (PGM)
- Laser Warning Systems (LWS)
- Laser Range Finding (LRF)
- Laser Spot Tracking
- Laser Alignment
- Position Sensor

Table 1. Electro-Optical Common CharacteristicsConditions: $T_{case} = 25\text{ }^{\circ}\text{C}$, $V_{+} = 5.0\text{ V}$, $V_{-} = -5.0\text{ V}$, $V_{PIN} = 3.0$, $\lambda = 1570\text{ nm} \pm 10\text{ nm}$

Parameter	Symbol	Min.	Typ.	Max.	Units
Output impedance	R_{out}		50		Ω
Bandwidth, f_{-3dB}	BW		40		MHz
Rise time (10-90 %) & Fall time (90-10 %)	t_{rise}		10		ns
Linear Output Voltage Swing (Pulse)			1.0		V
Output Offset Voltage	V_{oo}	-0.1	0.0	0.1	V
Supply current V_{+}	I_{pos}		35		mA
Supply current V_{-}	I_{neg}		-65		mA
Channel-to-channel crosstalk			5		%
Channel uniformity				5	%

Table 2. Electro-Optical Characteristics for 2 mm quadrant diameterConditions: $T_{case} = 25\text{ }^{\circ}\text{C}$, $V_{+} = 5.0\text{ V}$, $V_{-} = -5.0\text{ V}$, $V_{PIN} = 3.0$, $\lambda = 1570\text{ nm} \pm 10\text{ nm}$

Parameter	Symbol	Min.	Typ.	Max.	Units
Responsivity					
1060 nm	R		6.0		kV/W
1550 nm			9.0		kV/W
Noise equivalent power (DC - 40 MHz) (Note 1)					
Dark conditions	NEP		12		$\text{pW}/\sqrt{\text{Hz}}$
1-sun background illumination			20		

Note: 1. Integration of the noise calculation is based on f_{-3dB} bandwidth.**Table 3. Electro-Optical Characteristics for 3 mm quadrant diameter**Conditions: $T_{case} = 25\text{ }^{\circ}\text{C}$, $V_{+} = 5.0\text{ V}$, $V_{-} = -5.0\text{ V}$, $V_{PIN} = 3.0$, $\lambda = 1570\text{ nm} \pm 10\text{ nm}$

Parameter	Symbol	Min.	Typ.	Max.	Units
Responsivity					
1060 nm	R		4.5		kV/W
1550 nm			6.5		kV/W
Noise equivalent power (DC - 40 MHz) (Note 1)					
Dark conditions	NEP		20		$\text{pW}/\sqrt{\text{Hz}}$
1-sun background illumination			30		

Note: 1. Integration of the noise calculation is based on f_{-3dB} bandwidth.

Table 3. Absolute-Maximum Ratings, Limiting Values

Parameter	Symbol	Min.	Max.	Units
Average photocurrent	I_{ave}		5	mA
Pre-amplifier Voltage V+	V_{pos}		6.5	V
Pre-amplifier Voltage V-	V_{neg}	-6.5		V
Quadrant PIN Breakdown Voltage	V_{br}		12	V
Operating Temperature	T_{op}	-40	85	°C
Storage Temperature	T_{stor}	-55	125	°C
Soldering Temperature (5 s, leads only)			250	°C

Figure 1. Typical Normalized Responsivity




Figure 2. Package Dimension and Pinout

Unless otherwise specified, dimensions are in inches (mm) and are for reference only.




Table 4. Ordering Guide

VAR	Typical Bandwidth	Active Diameter	Comments
264-339838-001	40 MHz	2 mm	
264-339838-001	40 MHz	3 mm	



For more information, visit www.cmcelectronics.ca/optoelectronics or email us at opto@cmcelectronics.ca

For information purposes only. To accommodate product improvements, specifications are subject to change without notice.

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION IS UNLIMITED
264-339838-VAR | Datasheet REV 04.2026